



Tycroc metal washer

APPLICATION

For fastening Tycroc building boards or other insulation materials and building boards to a framework or load-bearing substrate. For fastening Tycroc TWP building boards from 6 mm up to 80 mm thickness with a suitable fixing screw or also for fastening Tycroc UHP underfloor heating panels with a suitable fixing screw.

RATE OF CONSUMPTION

- For Tycroc TWP boards - minimum 15 pcs or 10 pcs/m² for 2500x600 mm board or minimum 20 pcs or 7 pcs/m² for 2500x1200 mm board.
- For fixing Tycroc UHP panels - at least 15 pcs or 21 pcs/m² with 1200x600 mm panel.

TECHNICAL DATA

PROPERTY	UNIT	VALUE
Dimensions	mm	36 x 0,6
Material		430 stainless steel
Packing	carton	50 pcs in carton

STORAGE

Store in a dry environment.

WASTE TREATMENT

Completely empty packaging and dispose of according to regulations.

SAFETY INFORMATION

Follow general building safety rules.

Attention! The instructions in the present documentation are based on tests carried out by the manufacturer and are presented in good faith. Due to variations in materials as well as the various application possibilities that are beyond our control, we are not liable for the results achieved. It is recommended to test product suitability at the place of application.