



Tycroc aluminium tape TAPE70

Tycroc aluminium tape is based on 70 µm aluminium foil and acrylic adhesive.

PRODUCT DESCRIPTION

- Mechanically strong
- Good adhesion
- High thermal conductivity
- Moisture resistant
- Resistant to steam
- Resistant to oils and acids

APPLICATIONS

- Installation of Tycroc UHP underfloor heating panels
- General purpose thermal insulation for both indoor and outdoor applications
- Hermetic sealing of cooling/heating systems

TECHNICAL DATA

Material	Aluminium foil
Thickness of the material	70 µm
Glue type	Acrylic
Elongation at break	2 %
Tensile strength	7.5 N / 25 mm
Temperature resistance MIN	-
Temperature resistance MAX	100

INSTRUCTIONS FOR USE

Apply to a clean, dry and dust-free surface.

STORAGE

Store at temperatures up to 21°C, away from direct sunlight.

PACKAGING

50 m x 45mm / roll, 42 rolls in carton

SAFETY INFORMATION

- Avoid prolonged skin contact.
- Keep out of reach of children.

Attention! The instructions in the present documentation are based on tests carried out by the manufacturer and are presented in good faith. Due to variations in materials as well as the various application possibilities that are beyond our control, we are not liable for the results achieved. It is recommended to test product suitability at the place of application.